Appl. No. 10/701,879

Amdt. Dated: October 24, 2007

Reply to Office Action mailed August 3, 2007

This listing of claims will replace all prior versions and listings of claims in the application:

Listing of Claims

- (Currently Amended) A process for producing a temperature sensitive natural filler-reinforced thermoplastic polymer composition as an article which comprises:
- (a) extrusion melt-forming through a die in a first extruder a mixture consisting essentially of a high melting temperature thermoplastic polymer melting at 200°C or above, which has been pre-dried to remove moisture, with a first melting temperature with a metal chloride, bromide or iodide salt, wherein the salt is present in an amount between about 2.5 and 5 percent by weight of the polymer which reduces the melting temperature of the mixture to a second lower melting temperature of less than 200°C to form first strands;
- (b) pelletizing the first strands to form pellets; and
- (c) extruding a mixture of a temperature sensitive natural filler, consisting essentially of cut fibers selected from the group consisting of a plant

Appl. No. 10/701,879

Amdt. Dated: October 24, 2007

Reply to Office Action mailed August 3, 2007

leaf, seed, stalk and eembination combinations thereof, and the pellets in a second extruder, at the second lower melting temperature of less than 200°C without degrading the natural filler to form second strands of the natural filler-reinforced thermoplastic polymer composition, wherein without the metal salt, the extrusion with the temperature sensitive filler degrades the temperature sensitive natural filler.

2. (Previously Presented) The process of Claim 1 wherein the fibers are selected from the group consisting of hemp, flax, kenaf, jute, sisal, pineapple leaf fiber, coir, henequen, corn, cotton, and mixtures thereof.

(Cancelled)

4. (Currently Amended) The process of Claim 1_7 or 2_7 or 3_7 wherein the thermoplastic polymer is selected from the group consisting of nylon, polyethylene terephthalate (PET), polybutylene terephthalate (PBT), polytrimethylterephthalate (PTT), ethylene carbon monoxide (ECM), propylene oxide (PPO), polystyrene copolymer blends, polyacetals, cellulose butyrate,

Appl. No. 10/701,879

Amdt. Dated: October 24, 2007

Reply to Office Action mailed August 3, 2007

acrylonitrile-butadiene-styrene (ABS), methyl methacrylates, polychlorotrifluoroethylene polymers, and mixtures thereof.

- 5. (Currently Amended) The process of Claim 1_7 or 2_7 or 3 wherein the metal in the metal salt forms a reaction product with the polymer in the melt.
- (Currently Amended) The process of Claim 17 or 27 08
 wherein the metal salt is a metal halide.
- 7. (Currently Amended) The process of Claim 1 wherein in addition the filler reinforced thermoplastic polymer composition is molded into a shape.

Claim 8 (Cancelled)

- 9. (Currently Amended) The process of Claim 1 wherein a glass or a high melting temperature polymer fiber is introduced with the fibers natural filler in step (c).
- 10. (Currently Amended) A process for producing an article from a temperature sensitive natural fibers-

MSU 4.1-617 Appl. No. 10/701,879

Amdt. Dated: October 24, 2007

Reply to Office Action mailed August 3, 2007

reinforced thermoplastic polymer composition which comprises:

- (a) extrusion melt-forming through a die in a first extruder a mixture consisting essentially of a high melting temperature thermoplastic polymer melting at 200°C or above, which has been pre-dried to remove moisture, with a first melting temperature with at least one metal salt selected from the group consisting of lithium chloride, lithium bromide, lithium iodide, copper chloride, zinc chloride, aluminum chloride, gallium chloride, and mixtures thereof wherein the salt reduces the melting point of the mixture to a second lower melting temperature of less than 200°C to form the first strands;
- (b) pelletizing the first strands to form second pellets;
- extruding a mixture of one or (c) temperature sensitive natural fibers. consisting essentially of cut fibers selected from the group consisting of a plant leaf, seed, stalk and combination combinations thereof, and the second pellets in a second extruder, at the second lower melting temperature of less than 200°C without degrading the natural fibers to form

Appl. No. 10/701,879

Amdt. Dated: October 24, 2007

Reply to Office Action mailed August 3, 2007

second strands of the temperature sensitive natural fibers-reinforced thermoplastic polymer composition; and

- (d) melt-forming an article from the composition of step (c), wherein the extruding and melt forming without the metal salt degrades the temperature sensitive natural fibers.
- 11. (Previously Presented) The process of Claim 10 wherein the fibers are selected from the group consisting of hemp, flax, kenaf, jute, sisal, pineapple leaf fiber, coir, henequen, corn, cotton, and mixtures thereof.
- 12. (Previously Presented) The process of Claim 10 wherein the fibers-reinforced composition further includes a maleated compatibilizer and one or more toughening agents selected from the group consisting of rubber, modified rubber, maleated rubber, epoxidized rubber, vegetable oil-based plasticizer, and mixtures thereof.
- 13. (Original) The process of Claim 10, 11, or 12 wherein the thermoplastic polymer is selected from the group consisting of nylon, polyethylene terephthalate (PET),

MSU 4.1-617 Appl. No. 10/701,879

Amdt. Dated: October 24, 2007

Reply to Office Action mailed August 3, 2007

polybutylene terephthalate (PBT), ethylene carbon monoxide (ECM), propylene oxide (PPO), polystyrene copolymer blends, polyacetals, cellulose butyrate, acrylonitrile-butadiene-styrene (ABS), methyl methacrylates, polychlorotrifluoroethylene polymers, and mixtures thereof.

- 14. (Original) The process of Claim 10, 11, or 12 wherein the metal in the metal salt forms a reaction product with the thermoplastic polymer in the melt.
- 15. (Previously Presented) The process of Claim 10 wherein the fibers-reinforced thermoplastic polymer composition is molded into a shape.

Claim 16 (Cancelled)

17. (Previously Presented) The process of Claim 10 wherein a glass or a high melting temperature polymer fiber is introduced with the fibers in step (c).

MSU 4.1-617 Appl. No. 10/701,879

Amdt. Dated: October 24, 2007

Reply to Office Action mailed August 3, 2007

for producing 18. (Currently Amended) A process temperature sensitive natural filler-reinforced thermoplastic polymer composition as an article which comprises:

- (a) extrusion melt-forming through a die in a first extruder a mixture consisting essentially of a thermoplastic polymer, which has been pre-dried to remove moisture, with a melting temperature at about 200°C or above with at least one metal chloride, bromide or iodide salt, wherein the salt is present in an amount between about 2.5 and 5 percent by weight of the polymer which reduces the melting temperature of the mixture to less than about 200° C to form the strands;
- (b) pelletizing the strands to form pellets; and
- (c) extruding a mixture of the temperature sensitive natural filler, consisting essentially of cut fibers selected from the group consisting of a plant leaf, seed, stalk and eembination combinations thereof, and the pellets in a second extruder, at less than 200° C without degrading the temperature sensitive natural filler to form second strands of the natural fillerreinforced thermoplastic polymer composition, wherein

Appl. No. 10/701,879

Amdt. Dated: October 24, 2007

Reply to Office Action mailed August 3, 2007

without the metal salt, the extrusion with the temperature sensitive filler degrades the temperature sensitive natural filler.

- 19. (Original) The process of Claim 18 wherein the thermoplastic polymer is selected from the group consisting of nylon, polyethylene terephthalate (PET), polybutylene terephthalate (PBT), polytrimethylterephthalate (PTT), ethylene carbon monoxide (ECM), propylene oxide (PPO), polystyrene copolymer blends, polyacetals, cellulose butyrate, acrylonitrile-butadiene-styrene (ABS), methyl methacrylates, polychlorotrifluoroethylene polymers, and mixtures thereof.
- 20. (Previously Presented) The process of Claim 18 wherein the filler is selected from the group consisting of hemp, flax, kenaf, jute, sisal, pineapple leaf fiber, coir, henequen, corn, cotton, and mixtures thereof.

Appl. No. 10/701,879

Amdt. Dated: October 24, 2007

Reply to Office Action mailed August 3, 2007

21. (Previously Presented) The process of Claim 18 wherein the metal salt is selected from the group consisting of lithium chloride, lithium bromide, lithium iodide, copper chloride, zinc chloride, aluminum chloride, gallium chloride, and mixtures thereof.

22. (Previously Presented) The process of Claim 18 wherein the filler further includes a glass or a high melting temperature polymer fiber.

Claims 23-29 (Cancelled)